



The Australian Pipe Company
 Printing date 02.08.2018

Safety Data Sheet

according to WHS Regulations

Revision: 02.08.2018

1 Identification

Product Name: PRECAST CONCRETE PRODUCTS AND PIPES

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use:
 Variety of applications in buildings and civil engineering projects.

Details of Manufacturer or Importer:
 Reinforced Concrete Pipes
 69-99 Ferris Road, Melton South 3338 (Vic)
 115 Pearson Road Yatala 4207 (Queensland)
 Lot 90, Cocos Drive, Bibra Lake 6163 (WA)
 149 Somersby Falls Rd, Somersby 2250 (NSW)

Phone Number:
 1800 887 272 (Vic)
 1800 887 272 (Qld)
 1800 887 272 (WA)
 1800 887 272 (NSW)

Emergency telephone number: National Poison Information Centre: 13 11 26

2 Hazard(s) Identification

Hazardous Nature:
 Not classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.
 Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)



corrosion

Serious Eye Damage/Irritation 1 H318 Causes serious eye damage.



Skin Corrosion/Irritation 2	H315 Causes skin irritation.
Skin Sensitisation 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.

Signal Word Danger

Hazard Statements
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.

Precautionary Statements
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash hands thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves / eye protection / face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.

Safety Data Sheet

according to WHS Regulations

Printing date 02.08.2018

Revision: 02.08.2018

Product Name: PRECAST CONCRETE PRODUCTS AND PIPES

(Contd. of page 1)

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national regulations.

Additional Information

This product is a solid article and is considered to be non-hazardous in its normal state.
The above hazards apply to dusts released during activities such as cutting or sanding.

3 Composition and Information on Ingredients

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:

CAS: 14808-60-7	Quartz (SiO ₂)	20 - 85%
	☠ Carcinogenicity 1A, H350; STOT RE 1, H372	
CAS: 65997-15-1	Cement, portland, chemicals	10 - 20%
	⚠ Serious Eye Damage/Irritation 1, H318; ⚠ Skin Corrosion/Irritation 2, H315; ⚠ Skin Sensitisation 1, H317; STOT SE 3, H335	

Additional information:

The value for quartz represents the total amount, not the respirable fraction.
Exposure to respirable silica is not expected during normal use, but if product is cut, sawn, crushed or abraded dust will be generated that may include respirable silica. The actual exposure to respirable crystalline silica must be determined by workplace assessment.

4 First Aid Measures

Inhalation:

If inhaled, remove to fresh air. Seek medical attention if breathing problems develop. If not breathing, give artificial respiration.

Skin Contact:

In case of skin contact, remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, hold eyelids open and rinse with water for at least 15 minutes. Seek medical attention if symptoms occur.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give a glass of water. Never give anything by mouth to an unconscious person. Seek medical attention if symptoms occur.

Symptoms Caused by Exposure:

Inhalation: Dust may cause irritation to the nose, throat and lungs, leading to coughing and sneezing.

Skin Contact: Dust causes skin irritation. May cause skin drying or allergic skin reaction.

Eye Contact: Dust causes serious eye damage, redness and watering.

Ingestion: Ingestion is unlikely during normal use. May be abrasive and irritating to the mouth and throat.

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 02.08.2018

Revision: 02.08.2018

Product Name: PRECAST CONCRETE PRODUCTS AND PIPES

(Contd. of page 2)

5 Fire Fighting Measures

Suitable Extinguishing Media: Use fire extinguishing methods suitable to surrounding conditions.

Specific Hazards Arising from the Chemical:

This product is not flammable or combustible, but toxic gases may be released if strongly heated. Product close to fire should be removed only if safe to do so.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved dust/particulate filter respirator and full protective clothing. Evacuate all non-essential personnel from affected area. Do not breathe dust. Ensure adequate ventilation. Avoid generating dust.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Pick up large pieces and clean up the small pieces and dust with a vacuum or by a wet sweeping technique. Do not use compressed air. Wet down dust before clean up to minimise dust generation.

7 Handling and Storage

Precautions for Safe Handling:

Handling of this product should be carried out using good manual handling techniques. Use of safe work practices are recommended to avoid eye or skin contact and inhalation of dust. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Contaminated work clothing must not be allowed out of the workplace. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

No special requirements for storage. Risk assessments should be performed to ensure general safety of stockpiles.

8 Exposure Controls and Personal Protection

Exposure Standards:

CAS: 14808-60-7 Quartz (SiO₂)

WES	TWA: 0.1 mg/m ³ respirable dust
-----	---

CAS: 65997-15-1 Cement, portland, chemicals

WES	TWA: 10 mg/m ³
-----	---------------------------

Engineering Controls:

Where concrete dust is present it is necessary to maintain air concentration below occupational exposure standards, providing adequate ventilation.

Respiratory Protection:

Where an inhalation risk exists, wear a Class P1 (particulate) respirator. At high dust levels, wear a powered air purifying respirator (PAPR) with Class P3 (Particulate) filter or an air-line respirator or a full-face Class P3 (particulate) respirator. See Australian/New Zealand Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Standard duty leather, PVC or rubber gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 02.08.2018

Revision: 02.08.2018

Product Name: PRECAST CONCRETE PRODUCTS AND PIPES

(Contd. of page 3)

When selecting hand protection, the product should comply with relevant performance criteria. For example, gloves should meet a suitable level of abrasion resistance to provide protection against hazards of a workplace.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against dust. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 Physical and Chemical Properties

Appearance:

Form:	Solid concrete
Colour:	Grey
Odour:	Cementitious odour
Odour Threshold:	No information available
pH-Value:	>7.0
Melting point/freezing point:	>1200 °C
Initial Boiling Point/Boiling Range:	Not applicable
Flash Point:	Not applicable
Flammability:	Product is not flammable.
Auto-ignition Temperature:	Not applicable
Decomposition Temperature:	No information available
Explosion Limits:	
Lower:	Not applicable
Upper:	Not applicable
Vapour Pressure:	Not applicable
Relative Density:	2.5
Vapour Density:	Not applicable
Evaporation Rate:	Not applicable
Solubility in Water:	Not soluble, or slightly soluble. When mixed with water this product forms an alkaline solution (pH >11).
Partition Coefficient (n-octanol/water):	Not applicable
Viscosity:	Not applicable

10 Stability and Reactivity

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: No further relevant information available.

Incompatible Materials: No further relevant information available.

Hazardous Decomposition Products: No hazardous decomposition products known.

11 Toxicological Information

Toxicity:**LD₅₀/LC₅₀ Values Relevant for Classification:**

Oral	LD ₅₀	>5000 mg/kg
------	------------------	-------------

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing date 02.08.2018

Revision: 02.08.2018

Product Name: PRECAST CONCRETE PRODUCTS AND PIPES

(Contd. of page 4)

CAS: 14808-60-7 Quartz (SiO₂)		
Oral	LD ₅₀	500-22,500 mg/kg (rat)

Acute Health Effects**Inhalation:** Dust may cause irritation to the nose, throat and lungs, leading to coughing and sneezing.**Skin:** Dust causes skin irritation. May cause skin drying or allergic skin reaction.**Eye:** Dust causes serious eye damage, redness and watering.**Ingestion:** Ingestion is unlikely during normal use. May be abrasive and irritating to the mouth and throat.**Skin Corrosion / Irritation:** Causes skin irritation.**Serious Eye Damage / Irritation:** Causes serious eye damage.**Respiratory or Skin Sensitisation:** May cause an allergic skin reaction.**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:**

Silica dust, crystalline, in the form of quartz or cristobalite is classified by IARC as Group 1 - Carcinogenic to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:** May cause respiratory irritation.**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.**Chronic Health Effects:**

Prolonged eye contact may cause inflammation of the cornea.

Repeated or prolonged skin contact may cause skin dryness, reddening and irritation leading to dermatitis.

Dusts may contain respirable silica. The prolonged and repeated exposure (by inhalation) to respirable (crystalline) silica cause silicosis, a debilitating lung disease. The crystalline silica dust is practically insoluble in body fluids and can be deposited in lungs. Cigarette smoking can reduce the clearance of crystalline silica. The data indicate that the relative lung cancer risk is increased for people with silicosis.

Existing Conditions Aggravated by Exposure:

Pre-existing respiratory conditions, such as asthma or bronchitis, may be aggravated by exposure to this product.

Persons who are allergic to chromium may develop allergic dermatitis.

Additional toxicological information: No information available

12 Ecological Information

Ecotoxicity:

No adverse ecological effects are expected.

Crushed product and dusts can form an alkaline mixture in water.

Aquatic toxicity: No further relevant information available.**Persistence and Degradability:** Product is persistent and not biodegradable.**Bioaccumulative Potential:** Bioaccumulation is not expected to occur.**Mobility in Soil:** This product is expected to have low mobility.**Other adverse effects:** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations

Printing date 02.08.2018

Revision: 02.08.2018

Product Name: PRECAST CONCRETE PRODUCTS AND PIPES

(Contd. of page 5)

13 Disposal Considerations

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14 Transport Information

UN Number Not regulated

Proper Shipping Name Not regulated

Dangerous Goods Class Not regulated

Packing Group: Not regulated

15 Regulatory Information

Australian Inventory of Chemical Substances:

CAS: 14808-60-7	Quartz (SiO ₂)
CAS: 65997-15-1	Cement, portland, chemicals
CAS: 69012-64-2	Silica-Amorphous Silica fume
CAS: 7732-18-5	Water

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:

Not Scheduled.

16 Other Information

Date of Preparation or Last Revision: 02.08.2018

Prepared by: MSDS.COM.AU Pty Ltd

www.msds.com.au

Abbreviations and acronyms:

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC₅₀: Lethal concentration, 50 percent

LD₅₀: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Skin Corrosion/Irritation 2: Skin corrosion/irritation – Category 2

Serious Eye Damage/Irritation 1: Serious eye damage/eye irritation – Category 1

Skin Sensitisation 1: Skin sensitisation, Hazard Category 1

Carcinogenicity 1A: Carcinogenicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - February 2016"

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Reinforced Concrete Pipes makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.