

# EKOPIPE

VICTORIA



## INTRODUCING EKOPIPE


With over a decade of research and development, EKOPIPE is a game-changing eco-friendly concrete pipe, utilising our revolutionary new BX3 technology, and it's here to change the future of our built and natural environment.

EKOpipe meets all performance and durability requirements from the AS4058 concrete pipe standard, and is manufactured using the same manufacturing process as standard SRCPipe. EKOpipe can be used wherever reinforced concrete pipe is required. With the same joint design, installation of EKOpipe can even be done in-line with standard SRCPipes.

## ABOUT **BX3**

BX3 technology uses an innovative approach to produce a low-carbon pipe without compromising the known properties of reinforced concrete pipes.

# EKOPIPE | RUBBER RING JOINT




Nom. ID (mm)	Pipe ID (mm)	Socket OD (mm)	Pipe OD (mm)			Weight (kg)		
			Class 2	Class 3	Class 4	Class 2	Class 3	Class 4
225	220	370	-	-	298	-	-	210
300	295	455	-	-	371	-	-	260
375	370	546	-	-	452	-	-	340
450	445	643	-	-	545	-	-	500
525	520	734	-	-	660	-	-	800
600	595	825	-	-	726	-	-	860
675	670	913	790	790	850	890	900	1300
750	745	1005	878	878	905	1080	1090	1290
825	820	1094	960	960	1008	1230	1230	1630
900	895	1185	1048	1075	1075	1470	1710	1730
1050	1045	1344	1198	1235	1235	1750	2160	2160
1200	1195	1532	1368	1405	1405	2280	2720	2720
1350	1345	1690	1528	1564	1564	2680	3220	3240
1500	1495	1910	1680	1730	1730	3240	3890	3920
1650	1645	2056	1840	1935	1935	3600	5020	5040
1800	1795	2226	1995	2105	2105	4100	5870	5900
2100	2095	2556	2300	2400	2400	5000	6770	6790

\*Dimensions and weights subject to change

- Effective length = 2340mm
- Rubber rings supplied with all pipes
- Other classes available on request
- Pipes listed above conform with AS/NZS 4058:2007 for normal environment exposure conditions
- Marine or aggressive environment pipes available upon request

# EKOPIPE | FLUSH JOINT



Nom. ID (mm)	Pipe ID (mm)	Pipe OD (mm)			Weight (kg)		
		Class 2	Class 3	Class 4	Class 2	Class 3	Class 4
675	670	791	791	855	790	790	1270
750	745	874	874	906	940	940	1200
825	820	961	961	1005	1130	1140	1530
900	895	1046	1046	1076	1320	1320	1630
1050	1045	1195	1238	1238	1530	1980	2010
1200	1195	1356	1396	1396	1900	2360	2370
1350	1345	1520	1580	1580	2280	2810	2850
1500	1495	1680	1730	1730	2710	3470	3480
1650	1645	1830	1910	1910	3020	4290	4320
1800	1795	1990	2080	2070	3550	4980	5000
2100	2095	2334	2400	2400	4750	6180	6260

\*Dimensions and weights subject to change

- Effective length = 2340mm
- Sealing bands available on request
- Other classes available on request
- Pipes listed above conform with AS/NZS 4058:2007 for normal environment exposure conditions
- Marine or aggressive environment pipes available upon request



## GET IN TOUCH

Please contact RCPA

**1800 88 7272**

**[repa.com.au](http://repa.com.au)**